REZNOR®



Garage Heater

WHY HEAT YOUR GARAGE?

- » KEEP YOUR CHILDREN AND INFANTS WARM WHILE TRANSFERRING FROM HOME TO CAR
- » STORE COLD SENSITIVE MATERIAL
- » KEEP OUTDOOR PLANTS AND PETS WARM DURING WINTER STORMS
- » AVOID HAVING TO LET YOUR CAR IDLE TO LET IT WARM UP – REDUCE RISK OF CARBON MONOXIDE BUILD-UP
- » MAINTAIN GARAGE EITHER AT COMFORTABLE TEMPERATURE OR JUST ABOVE FREEZING







What is the Reznor Edge?

The Reznor Edge: WHY A REZNOR HEATER?

Experience - Reznor is THE name in reliability ever since the first Reznor Heater was developed over 125 years ago.

Distribution - Reznor Heaters can be found in-stock at 2,000 distributor locations throughout North America

Innovation - Ever since the first reflector heater was invented in 1888, Reznor HVAC equipment has constantly been at the forefront of technological breakthroughs. This is evident in the V3® garage heater with the Tcore^{2®} combustion system.





Compact, Aesthetic Concentric Vent/Combustion Air Horizontal Vent Kit

Features	Benefits		Model UDAS
Low Profile	Compact design improves overhead clearance, allowing for more headroom than conventional unit heaters.	Υ	Υ
Titanium Stabilized, Corrosion Resistant Aluminized Steel Heat Exchangers	Heating elements in the units are designed to provide long life. Heat exchangers are backed by a 10 year warranty (parts only, see limited warranty form for complete details). Stainless steel heat exchangers also available.	Υ	Υ
Single, One-Piece Burner Assembly ^A	Patented TCORE ^{2®} developed by Reznor provides you the highest efficiency of any unit heater in this class. Higher efficiency (up to 83% efficiency) means less natural gas/propane is needed, saving you money.	Υ	Υ
Separated Combustion ^B	Air for combustion is drawn from the outside. This increases seasonal efficiency by keeping heated air inside the space instead of using it for combustion, and exhausting it to the outdoors.		Υ
Spark Ignitor - No Standing Pilot	An electronic pilot instead of the old style, standing pilot which could be blown out when a garage door is open on windy days.	Υ	Υ
Power Vented	A small blower is used to force exhaust gases through the flue. This makes the heater more efficient. A smaller flue pipe is required which also saves you money on installation costs.	Υ	Υ
Horizontal or Vertical Flue Venting	The flue pipe can run vertically through the ceiling/roof in the traditional method, or it can run horizontally through a side wall when vertical venting is not practical.	Υ	Υ
Separate Wall Thermostat	The garage heater can be operated independently from the home furnace by a separate thermostat mounted in the garage.	Υ	Υ
Multiple Fuels	Heater can use natural gas or propane (Conversion kit may be required).	Υ	Υ
Integrated Circuit Board with LED Diagnostic Indicator Light	Designed to assure safe reliable operation and easy maintenance.	Υ	Υ
Quiet Operation	Fan and venter motor isolation result in quietest published sound data.	Υ	Υ
International Approval Standards ^c	Be sure to use only units approved for Installation in residential garages.	Y	Υ

^A U.S. Patent No. 6,889,686

For complete catalog information including submittals, energy calculations, dimension drawings, and more go to ReznorHVAC.com or call 800-695-1901.

Specifications & illustrations subject to change without notice or incurring obligations. O'Fallon, MO (9/17) © Nortek Global HVAC, LLC 2017. All rights reserved. Reznor is a registered trademark of Nortek Global HVAC, LLC. Printed in U.S.A.



076F-0917 (Replaces RE-GH-0614 Version H.1)



^B Keeping combustion air separate from air in the space is very important if you plan on auto repair, restoration, woodworking, stripping paint, refinishing furniture, or storing certain chemicals in your garage/shop.

^c CSA International Requirement 10.96- U.S. and CR96-0005 - Canada